

Bio Energetic Field Enhancement

energy through water Q² ENERGYTM spa

Model 4105

The Q2 ENERGYspa™ was created to realign, balance and enhance the bio energetic levels in water that is then used by the cells of all living things. Designed in Australia it leads the world in non invasive energetic hydro-therapy technology.

The model 4105, is the flagship ENERGYspa, providing increased functionality through computer controlled circuitry.

This circuitry provides custom self adjustment, by automatically selecting the correct energy output for your water conditions. Other innovative features include self protection and self system diagnostics with a numerical action coded display, and a built in timer which will turn off the unit when the session time is up. These are but a few of the features of the 4105 to make it a very powerful tool for the professional user. Best of all, this model comes with Not 1 but 2 Orb's, making it easier to use in a practice or relaxation clinic, giving you a backup unit to use while the other Orb is being cleaned, "no downtime". Designed to meet the International Electrical Equipment Isolation Safety Standards, IEC60601.1 with consideration to the international wiring rules with variations to suit Europe, USA, Canada and Australia.

The model 4105 power supply is double insulated, designed & built to comply with CE mark & UL requirements.

Improved Clarity

Improvement to the circuitry and components for this model now produce a much cleaner source of power to the Orb which means better quality for you. As an added benefit this prolongs the life of your consumables.

DVD Multimedia Presentation

The Q2 ENERGYspa™ comes packaged with a multimedia presentation. This presentation contains live video coverage of events and best of all, it contains video footage of "How to Use" the Q2 ENERGYspa™ and maintain the unit yourself.

The model 4105 includes;

- Innovative Q2 Orb x 2
- 20 Positive Ring & Track Sets
- Connection Cable x 2
- Spare Fuses
 - 2 x 4Amps, 250V (F4AL250V)
 - 2 x 2Amps, 250V (F2AL250V)
- User Manual
- Quick Reference Guide
- Multimedia DVD Presentation
- Carry Bag
- Warranty Information Card
- Information Guide

Technical

- Hardware ungradable
- Flash bios (software ungradable)
- Optimal level selection (auto adjusts to water quality)
- Automated system diagnostics
- Built in self protection & safety cutout
- Built in timer
- Improved Bio-Energy Enhancement
- Improved Electrical Signal Clarity
- Built to International Electrical Safety
- Isolation Standards IEC60601.1
- Compliance to CE Mark

CLASS II Equipment, Type B Applied Part
Safety extra low voltage isolating DC Power Supply.

Input: 100 to 120Vac 50/60Hz, 95W or
200 to 240Vac 50/60Hz, 95W
As indicated on the power supply.

Output: Isolated, Rectified and Filtered, 28Vdc, 3Amps.

Dimensions: 190x135x103mm

Weight: 2.8Kg (6.2 lbs)



Q - THE EXPERIENCE
feel the future
Leaders in Hydro Energetic Technologies



Optimal Health Equipment
OptimalHealth2000.com • 877-427-1600